



Plug & View



Free EdiView viewer app for
iPhone & Android phones

IC-3110 / IC-3110P / IC-3110W

1.3Mpx H.264 Day & Night Network Camera Fast Ethernet / PoE / Wireless



The Edimax IC-3110 series network camera is a versatile monitoring device ideal for monitoring your home in daylight and at night. With Edimax's innovative Plug-n-View technology, the camera connects to the cloud automatically, so you can monitor your home with a smartphone, tablet, or laptop computer no matter where you are. Its motion-triggered snapshot and recording feature ensures that you capture every criminal event. The IC-3110 series comes in three network interfaces (Fast Ethernet, wireless & PoE), making it perfect for any home monitoring application.

Edimax Plug-n-View

Edimax Plug-n-View technology makes it easy for you to keep an eye on the safety of your home, family, pets, and assets wherever you go. With Plug-n-View technology, you can set up your Edimax network camera in a few simple steps. The camera also connects to the cloud automatically, so you can access it remotely with a smartphone, tablet, or computer no matter where you are.

Night Vision

The built-in IR (infrared) LEDs and light sensor make this Edimax network camera perfect for capturing crisp and clear videos in low light conditions. It automatically switches to night vision mode and turns on the IR LEDs to illuminate the monitored area when it gets dark, ensuring that you get video footage of critical moments both in daylight and at night.

Motion-Triggered Snapshots & Recording

The powerful multi-area motion detection system built into this network camera ensures that you have evidence of a criminal event as soon as it occurs. You can pre-define multiple areas in the monitored range for motion detection; and when motion is detected in the specified areas, this network camera will produce snapshots or video footage of the criminal event immediately.

FEATURES & TECHNICAL SPECIFICATIONS

- High-speed triple-mode (H.264, MPEG-4 & M-JPEG) video compression
- Night vision support with built-in IR LED
- Multi-area motion detection
- SDHC/SD card slot for local snapshot and video storage
- 2-way audio, UPnP & DDNS support
- Remote monitoring via iPhone, iPad, Android phones, PC & Mac

Video / Audio	Standards	LED Indicators
<ul style="list-style-type: none"> • 1.3 megapixel CMOS sensor • 1.0 lux • 5mm, f/2.8 • Recording format: AVI • Video compression: H.264, MPEG-4 & M-JPEG • 2-way audio 	<ul style="list-style-type: none"> • Fast Ethernet IEEE 802.3/802.3u • Wireless IEEE 802.11b/g/n (IC-3110W only) • PoE IEEE 802.3af (IC-3110P only) 	<ul style="list-style-type: none"> • LAN • Wi-Fi (IC-3110W only) • Power/Cloud
Interface	Management	RF Output Power
<ul style="list-style-type: none"> • 1 x Ethernet (RJ-45) port • 1 x Power jack • 1 x Audio output • 1 x Microphone • 1 x Reset/WPS button (IC-3110W only) • 1 x SDHC/SD card slot (up to 32GB) • 1 x USB port for Wi-Fi adapter (IC-3110 only) • 1 x Detachable antenna (IC-3110W only) 	<ul style="list-style-type: none"> • EdiView Finder (Windows/Mac) • 16-channel viewer • Web management interface • Firmware upgradable • iPhone & iPad viewer app • Android phone viewer app 	<ul style="list-style-type: none"> • 11b: 16dBm - 18dBm • 11g: 14dBm - 16dBm • 11n: 11dBm - 13dBm (IC-3110W only)
Memory	Frequency Band	Temperature & Humidity
<ul style="list-style-type: none"> • 4MB flash • 64MB SDRAM 	<ul style="list-style-type: none"> • 2.4000 - 2.4835GHz (IC-3110W only) 	<ul style="list-style-type: none"> • 0-40° Celsius • 10-90% (non-condensing)
Power	Dimensions	Certifications
<ul style="list-style-type: none"> • 12V DC 	<ul style="list-style-type: none"> • 113mm x 80mm x 43mm 	<ul style="list-style-type: none"> • CE, FCC

NETWORK SETUP DIAGRAM AND RELATED PRODUCTS

