



SuperSpeed USB 3.0
Faster transfers



USB-C Connector
Reversible and easy to plug in



Plug & Play
No drivers installation required



High Compatibility
Support Windows, Mac, and Linux systems

USB-C to 3-Port USB 3.0 Gigabit Ethernet Hub

Introduction

With features of USB-C to 3-port SuperSpeed USB 3.0 Hub and Ethernet Adapter, the Edimax EU-4308 can transfer data to and from multiple devices at up to 5 Gbps. Enjoy high-speed data transfer and internet connection in one slim and lightweight Hub. Its multi-purpose is perfect for the latest tablets and ultra-thin laptops (with limited ports) to connect up to 3 USB devices and an Ethernet cable at once.



Reversible USB-C Connector



Type-C to 3-Port USB 3.0 Hub
with
Gigabit Ethernet Adapter

New Trend of USB Connectivity

- ❖ USB-C Compatible: works with the latest computers and smart devices with USB-C ports.
- ❖ SuperSpeed Data Transfer: up to 5 Gbps data speeds
- ❖ 3-port High-speed USB 3.0 extension and supports hot plug
- ❖ High Speed Ethernet: adapt to 10M/100M/1000Mbps bandwidth ethernet port which provides access to superfast network speeds
- ❖ Portable, lightweight design for travel or desktop placement
- ❖ Simple Installation: supports plug and play with no external drivers required
- ❖ Supports Windows, Mac, Linux Systems

2-in-1 Function. Plug and Play.

If your smart device is missing the ports you need, the EU-4308 can help. The 3-port USB 3.0 hub gives you access to not only your USB peripheral devices but also a wired internet connection. It offers a Gigabit Ethernet port, so you can connect to a network in locations where Wi-Fi is unreliable or unavailable.

2-in-1

Type-C to USB 3.0
Hub & LAN Port



Works with the Mainstream Operating System

No compatibility problems while using EU-4308 with your latest smart devices. The EU-4308 supports mainstream operating systems, including Windows, Mac OS, and Linux while keeping good performance in daily networking life.



SPECIFICATIONS

EU-4308 USB-C to 3-Port USB 3.0 Gigabit Ethernet Hub

HARDWARE

- | | |
|-------------------|--|
| Interface | <ul style="list-style-type: none">• 1 x USB 3.1 type C• 3 x USB 3.0 type A• 1 x RJ-45 10/100/1000Mbps LAN port |
| LED Indicator | <ul style="list-style-type: none">• Power, 10/100M, 1000M, USB3.0 |
| Connector | <ul style="list-style-type: none">• USB Type-C |
| Dimension | <ul style="list-style-type: none">• 77(L)mm x 46(W)mm x 14.5(H)mm |
| Weight | <ul style="list-style-type: none">• 45g |
| Power Consumption | <ul style="list-style-type: none">• 1A @5.0VDC (USB Bus Powered) |

WIRELESS

- | | |
|-----------|--|
| Standards | <ul style="list-style-type: none">• IEEE 802.3• IEEE 802.3u• IEEE 802.3ab• IEEE 802.3az• IEEE 802.1x/q |
|-----------|--|

OTHERS

- | | |
|---------------------|---|
| Certification | <ul style="list-style-type: none">• CE, FCC, RoHS |
| System Requirements | <ul style="list-style-type: none">• Intel Pentium III 1GHz (above or similar)• 256MB RAM / CD-ROM / 100MB Hard Disk Space (at least) / USB-C Port• Windows XP/Vista/7/8/8.1/10, Mac OS 10.6~10.10, Linux kernel 4.x/3.x/2.6.x |
| Environment | <ul style="list-style-type: none">• Operating Temperature: 0°C~40°C (32°F ~104°F)• Storage Temperature: -40°C~70°C (-4°F ~158°F) |
| Package Contents | <ul style="list-style-type: none">• 1 x EU-4308 USB-C to 3-Port USB 3.0 Gigabit Ethernet Hub• 1 x Quick Installation Guide• CD (Multi-Language Quick Installation Guide) |