





SuperSpeed USB 3.0 Faster transfers



**USB-C Connector**Reversible and easy to plug in



Plug & Play No drivers installation required



**High Compatibility**Support Windows, Mac, and Linux systems

Reversible USB-C Connector

# **USB-C to 3-Port USB 3.0 Gigabit Ethernet Hub**

#### Introduction

With features of USB-C to 3-port SuperSpeed USB 3.0 Hub and Ethernet Adapter, the Edimax EU-4308 can transfer data to and from multiple devices at up to 5 Gbps. Enjoy high-speed data transfer and internet connection in one slim and lightweight Hub. Its multi-purpose is perfect for the latest tablets and ultra-thin laptops (with limited ports) to connect up to 3 USB devices and an Ethernet cable at once.



Type-C to 3-Port USB 3.0 Hub with Gigabit Ethernet Adapter

## **New Trend of USB Connectivity**

- ❖ USB-C Compatible: works with the latest computers and smart devices with USB-C ports.
- SuperSpeed Data Transfer: up to 5 Gbps data speeds
- ❖ 3-port High-speed USB 3.0 extension and supports hot plug
- ❖ High Speed Ethernet: adapt to 10M/100M/1000Mbps bandwidth ethernet port which provides access to superfast network speeds
- ❖ Portable, lightweight design for travel or desktop placement
- Simple Installation: supports plug and play with no external drivers required
- Supports Windows, Mac, Linux Systems



# 2-in-1 Function. Plug and Play.

If your smart device is missing the ports you need, the EU-4308 can help. The 3-port USB 3.0 hub gives you access to not only your USB peripheral devices but also a wired internet connection. It offers a Gigabit Ethernet port, so you can connect to a network in locations where Wi-Fi is unreliable or unavailable.



# **Works with the Mainstream Operating System**

No compatibility problems while using EU-4308 with your latest smart devices. The EU-4308 supports mainstream operating systems, including Windows, Mac OS, and Linux while keeping good performance in daily networking life.



















#### **SPECIFICATIONS**

EU-4308 USB-C to 3-Port USB 3.0 Gigabit Ethernet Hub

HARDWARE	
Interface	• 1 x USB 3.1 type C
	• 3 x USB 3.0 type A
	• 1 x RJ-45 10/100/1000Mbps LAN port
LED Indicator	• Power, 10/100M, 1000M, USB3.0
	• USB Type-C
Dimension	• 77(L)mm x 46(W)mm x 14.5(H)mm
Weight	• 45g
Power Consumption	• 1A @5.0VDC (USB Bus Powered)

$\Omega$ T	ш	ERS
UΙ	ш	ヒハン

Standard	ds •	IEE	F 8	02.3
----------	------	-----	-----	------

• IEEE 802.3u

• IEEE 802.3ab

• IEEE 802.3az

IEEE 802.1x/q

#### Certification • CE, FCC, RoHS

#### System Requirements • Intel Pentium III 1GHz (above or similar)

• 256MB RAM / CD-ROM / 100MB Hard Disk Space (at least) / USB-C Port

 Windows XP/Vista/7/8/8.1/10, Mac OS 10.6~10.10, Linux kernel 4.x/3.x/2.6.x

#### Environment

- Operating Temperature: 0°C~40°C (32°F~104°F)
- Storage Temperature: -40°C~70°C (-4°F ~158°F)

### **Package Contents**

- 1 x EU-4308 USB-C to 3-Port USB 3.0 Gigabit Ethernet Hub
- 1 x Quick Installation Guide
- CD (Multi-Language Quick Installation Guide)